

# LED MINI T5 TUBE LIGHTS

## QUICK SEARCH: SC6846



### FEATURES:

- Ballast Bypass Option requires bypass or removal of ballast
- Solid State LED lighting
- Hours Rated: 50,000
- All glass tube
- Miniature Bi Pin (G5)
- Lens: Frosted




### INSTALLATION:

Double Sided Bypass



### DIMENSIONS:



### WARRANTY & LISTINGS:

- 5-year warranty
- cULus / UL listed
- Damp
- RoHS Compliant
- FCC Compliant
- NSF Approved

### ELECTRICAL:

- 120-277V
- CRI: 82
- Beam spread: 240
- Operating Frequency: 50/60 Hz
- Operating temperature: -25C (-13F) to a maximum of +45C (+113F)
- Power Factor: 0.9
- Non-Dimmable

### SPECIFICATION:

Product Code	Wattage	Lumens	Color Temperature	Dimensions
S11901	2W	150 Lumens	6500K Daylight	5.91" (L) x 0.83" (D)
S11900	2W	150 Lumens	4000K - Cool White	5.91" (L) x 0.83" (D)
S11903	3W	270 Lumens	6500K Daylight	8.91" (L) x 0.83" (D)
S11902	3W	270 Lumens	4000K - Cool White	8.91" (L) x 0.83" (D)
S11906	4W	400 Lumens	6500K Daylight	11.91" (L) x 0.83" (D)
S11905	4W	400 Lumens	4000K Cool White	11.91" (L) x 0.83" (D)
S11904	4W	400 Lumens	3000K Soft White	11.91" (L) x 0.83" (D)
S11909	7W	700 Lumens	6500K Daylight	20.91" (L) x 0.83" (D)
S11908	7W	700 Lumens	4000K Cool White	20.91" (L) x 0.83" (D)
S11907	7W	700 Lumens	3000K Soft White	20.91" (L) x 0.83" (D)