

LED EYEBALL DOWNLIGHT

SEARCH CODE: SC12520




FEATURES:

- Hole cutout diameter: ≈4 inch and ≈6 inch
- CCT Selectable: 2700K, 3000K, 3500K, 4000K, and 5000K.
- Finish: White or Black
- 360 Degree Rotation
- 0 to 80 Degree aiming angle
- Long life, 50,000 hours
- Dimmable
- Indoor rated only

DIMENSIONS:

4 inch:
(W) 4.92" x (H) 1.42

6 inch:
(W) 7.48" x (H) 2.17"



WARRANTY & LISTINGS:

- 5-year warranty
- Energy Star Certified
- cETLus - Listed
- Dimmable
- Air Tight Rated
- RoHS Compliant
- FCC Compliant

ELECTRICAL:

- Voltage: 120V
- CRI: 90
- Beam angle: 4 inch: 36° and 6 inch: 40°
- Operating Temperature: -20C (-4F) to +45C (+113F)

APPLICATION:

- Shallow Ceilings
- Cabinets
- Low-clearance basement ceilings

SPECIFICATIONS:

Product Code	Shape	Wattage	Lumens	Color Temperature	Size	Finish
S11840	Round	9W	650L-750L	CCT 27K, 3K, 35K, 4K, 5K	4inch	White
S11841	Square	9W	650L-750L	CCT 27K, 3K, 35K, 4K, 5K	4inch	White
S11842	Round	9W	650L-750L	CCT 27K, 3K, 35K, 4K, 5K	4inch	Black
S11843	Square	9W	650L-750L	CCT 27K, 3K, 35K, 4K, 5K	4inch	Black
S11860	Round	15W	1280L-1400L	CCT 27K, 3K, 35K, 4K, 5K	6inch	White
S11861	Square	15W	1280L-1400L	CCT 27K, 3K, 35K, 4K, 5K	6inch	White
S11862	Round	15W	1280L-1400L	CCT 27K, 3K, 35K, 4K, 5K	6inch	Black
S11863	Square	15W	1280L-1400L	CCT 27K, 3K, 35K, 4K, 5K	6inch	Black