

LED SQUARE SCONCE WALL LIGHTS

SEARCH CODE: SC12383




Available Colors



FEATURES:

- Finish: Black, Bronze, Brushed Nickel & White
- Multi CCT (Selectable Switch on the Bottom of the Arm, Protected by Silicon Cover to be Waterproof)
- Beam Angle: 45° Degrees

DIMENSIONS:



WARRANTY & LISTINGS:

- 5-Year warranty
- Wet location rated
- ETL listed

ELECTRICAL:

- Voltage: 4 inch models are 120V only
- Voltage: 5 inch models are 120-277V
- Dimming: 4 inch models compatible with standard TRIAC dimmers
- 5 inch models on 120V can use TRIAC or 0-10V dimmers, while on 277V can only use 0-10V dimmers.
- Power Factor: >0.95
- Efficacy: 80 LPW
- THD: <20%
- Housing: Die-cast Aluminum & Glass
- Maximum Ambient Temperature: 0°F to 104°F

APPLICATION:

- General site lighting
- Walkways, and stairways
- Alleys

SPECIFICATIONS:

Size	Wattage	Lumens	Color Temperature	Finish	Dimensions
4 Inch	12W Downlight	960 LM	Color Temperatures: 3000K/4000K/5000K	Black Bronze Brushed Nickel White	(H) 8" (W) 3.5" x (D) 5.875"
4 Inch	24W (Up/Down light, 12W per end)	1920 LM			(H) 10.25" (W) 3.5" x (D) 5.875"
5 Inch	20W Downlight	960 LM			(H) 8" x (W) 4.75" (D) 7.25"
5 Inch	40W (Up/Down light, 20W per end)	1920 LM			(H) 12" (W) 4.75" (D) 7.25"

LED SQUARE SCONCE WALL LIGHTS


SEARCH CODE: SC12383



4 INCH DIMENSIONS:

12W Downlight


(H) 8" (W) 3.5" x (D) 5.875"



4 INCH DIMENSIONS:

24W (Up/Down light, 12W per end)


(H) 10.25" (W) 3.5" x (D) 5.875"



5 INCH DIMENSIONS:

20W Downlight

(H) 8" x (W) 4.75" (D) 7.25"



5 INCH DIMENSIONS:

40W (Up/Down light, 20W per end)

(H) 12" (W) 4.75" (D) 7.25"

